



Technical Specification for SDS 48				در شرایط مناطق گرمسیری	در شرایط مناطق معتدل	
Function				Cooling / Heating	Cooling / Heating	
Capacity				Btu/h	42000 / 53000	
Total power input				W	5600 / 5130	
EER or COP				W/W	2.22 / 3.02	
Running /Max.Running current				A / A	9.7 A / 9.33 A	
Indoor unit	Power source			PH, V, Hz	3PH,380-415V,50Hz	
	Air Flow Volume			m <sup>3</sup> /hr	2400 / 2000 / 1600	
	ESP(Static head)			Pa	50 / 80	
	Dimension	External	L×W×H	mm×mm×mm	1250 × 785 × 290	
	Noise level	( H-M-L )		dB(A)	53 / 50 / 44	
	Weight				kg	52
Outdoor unit	Power source			PH, V, Hz	3PH,380-415V,50Hz	
	Fan	Air Flow Volume		m <sup>3</sup> /hr	6400	
	Dimension	External	L×W×H	mm×mm×mm	940 × 340 × 1320	
	Noise level				dB(A)	60
	Weight				kg	101
PIPING	Refrigerant	Type		R410A		
	Between I.D & O.D	MAX.Drop		m	30	
		MAX.Piping length		m	50	