

جدول تغییر ظرفیت برج های خنک کننده مدل SPC - SX

W.B °F	65	70	70	72	72	75	75	75	75	77	78	80
IN WATER °F	90	90	95	92	95	95	97	90	94	95	95	95
OUT WATER °F	80	80	85	82	85	85	87	83	85	85	85	85
Model	Flow Rate (GPM)											
SPC 100 SX	438	—	484	—	462	361	440	352	377	—	—	—
SPC 150 SX	570	396	650	423	595	357	572	440	468	400	361	—
SPC 200 SX	730	495	860	528	750	572	737	550	583	495	440	352
SPC 225 SX	910	560	1000	616	935	677	902	660	688	572	506	396
SPC 300 SX	1230	726	1386	768	1298	902	1255	880	924	726	660	495
SPC 400 SX	1510	946	1475	1012	1550	1166	1496	1100	1188	946	792	594
SPC 450 SX	1760	1080	1892	1210	1826	1364	1782	1320	1386	1078	946	688
SPC 600 SX	2275	1475	2640	1584	2376	1815	2288	1760	1848	1485	1364	935
SPC 800 SX	2870	1935	3255	2046	3015	2244	2905	2200	2332	1925	1782	1320
SPC 900 SX	3080	2110	3652	2255	3300	2530	3170	2420	2596	2112	1914	1430
SPC 1000 SX	3260	2245	3970	2420	3610	2684	3432	2640	2728	2255	2024	1496
SPC 1200 SX	4550	2595	4710	2728	4390	2905	4092	2860	2992	2596	2266	1738